



| DN | NPS | Kettenrad Chain wheel Typ / type | ØA | ØAK | B | C | D | E | F | G | ØK | ØL | ØM | T | kg |
|-----|-----|--|-----|-----|-----|-----|----|-----|-----|-----|-----|-------|-------|----|------|
| 50 | 2" | TRA - 1,5 | 200 | 223 | 121 | 91 | 43 | 384 | 252 | 110 | 125 | - | 4xM16 | 16 | 6,8 |
| 80 | 3" | TRA - 1,5 | 200 | 223 | 130 | 91 | 46 | 402 | 270 | 128 | 160 | 4xØ18 | 4xM16 | 18 | 9,8 |
| 100 | 4" | TRA - 1,5 | 200 | 223 | 148 | 96 | 52 | 468 | 335 | 138 | 180 | 4xØ18 | 4xM16 | 20 | 13,0 |
| 125 | 5" | TRA - 1,5 | 200 | 223 | 175 | 96 | 56 | 486 | 353 | 155 | 210 | 4xØ18 | 4xM16 | 22 | 15,0 |
| 150 | 6" | TRA - 2,5 | 250 | 286 | 200 | 104 | 56 | 606 | 467 | 179 | 240 | 4xØ22 | 4xM20 | 21 | 26,1 |
| 200 | 8" | TRA - 2,5 | 250 | 286 | 250 | 104 | 60 | 636 | 497 | 209 | 295 | 4xØ22 | 4xM20 | 23 | 32,1 |
| 250 | 10" | TRA - 2,5 | 300 | 286 | 328 | 141 | 68 | 799 | 643 | 240 | 350 | 6xØ22 | 6xM20 | 20 | 62,8 |
| 300 | 12" | TR - 3,5 | 400 | 459 | 378 | 141 | 78 | 834 | 673 | 270 | 400 | 6xØ22 | 6xM20 | 23 | 93,9 |

Max. Betriebsdruck:
 Max. working pressure:

| DN | Druck / pressure |
|---------|------------------|
| 50-150 | 10 bar |
| 200-300 | 6 bar |

Änderungen vorbehalten
 subject to changes